

275-Chlorine

Description:	PTFE based thread sealant
Temperature Range:	-50°F. to 400°F.
Features:	Non-Hardening, Non-Dripping, Corrosion Inhibiting, Self Lubricating, Non-Seizing Allows Disassembly Contains No Solvents, Non-Staining
Characteristics:	This is a non-curing compound with good lubricity and low friction characteristics. High Performance Thread Sealant. Easy to apply.
Chemical Compatibility:	Excellent, Inert to most solvents, acids, chemicals. For use on Chlorine Service.
Shelf Life:	Unlimited
Packaged:	8 oz.
Safety:	Due to the reactive nature of Chlorine, care should be taken not to contaminate sealant.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE.

NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS

Disclaimer: The information & recommendations of Jet-Lube LLC / Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Jet-Lube LLC / Deacon, the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Jet-Lube LLC / Deacon recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.

info@deaconindustries.com (800) 552-2896 or (724) 225-8008