

Date Prepared: February 1, 2017

1. **Product and Company Identification**

**Jet-Lube LLC / Deacon**  
**Bldg. #1, West Point Drive**  
**Washington, PA 15301 USA**  
**Phone (724) 225-8008**

**24 Hour Emergency Response Contact:**  
**CHEMTREC (USA and CANADA)**  
**Phone: 800-424-9300 or 703-527-3887**

Product Name: Deacon 500-L  
 Product Type: Sealant Compound  
 Product Description: Thin Brown Liquid  
 General Use : High Temperature Sealant

2. **Hazards Identification**

**GHS Classification :**

Skin Irritation, 2  
 Eye Irritation, 2B  
 Aspiration Hazard, 1

**GHS Label Elements :**

Signal Word : Warning



**Hazard Statements:**

H315 / 320 Causes Skin and Eye Irritation  
 H303 May be harmful if swallowed  
 H335 May cause respiratory irritation

**Precautionary Statements :**

P261 Avoid breathing dust/vapors  
 P262 Do not get in eyes, on skin, or on clothing  
 P285 In case of inadequate ventilation wear respiratory protection  
 P281 Use personal protective equipment as required  
 P301/P330/P331 If Swallowed : Rinse mouth, Do NOT induce vomiting.  
 P301/P310 If Swallowed: Immediately call a Poison Center or Physician  
 P333/P313 If skin irritation or rash develops: Get medical attention.  
 P302/P352 If on skin: Wash with plenty of soap and water  
 P305/P351/P338 If in eyes : Rinse cautiously with water for several minutes.  
 Remove contact lenses if easy to do. Continue Rinsing.  
 P337/P313 If eye irritation persists: Get medical attention  
 P342/P311 If experiencing respiratory symptoms : Get medical attention.  
 P233 Keep container tightly closed  
 P210 Keep away from open flames. – No Smoking  
 P501 Dispose of observing all Federal, State and Local regulations.

**3. Composition / Information on Ingredients**

Ingredients	CAS No.	% by weight
Solvent Mixture	64742-47-8	25-50
Modified Natural Resins	Proprietary	50-75

**4. First Aid Measures**

- Ingestion: DO NOT INGEST. Oral toxicity not determined. Do NOT induce vomiting. Even small amount of solvent aspirated into the lungs during ingestion or vomiting may cause aspiration pneumonitis. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or get medical help immediately.
- Inhalation: Remove to fresh air. If symptoms persist, seek medical attention.
- Skin Contact: Wash with soap and water, consult physician if rash develops.
- Eye Contact: Flush with water 15 minutes. If symptoms persist, seek medical attention.

**5. Fire Fighting Measures**

- Recommended Extinguishing Agent:  
Foam, Dry Chemical, Carbon Dioxide, Water Fog
- Special Fire Fighting Procedures:  
Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. (Professionally Trained Personnel).
- Hazardous Products Formed by Fire  
or Thermal Decomposition:  
CO, CO<sub>2</sub>, H<sub>2</sub>S, SO<sub>2</sub>, Smoke, Incomplete Combustion Products
- Unusual Fire or Explosion Hazards:  
Closed containers may rupture when exposed to extreme heat or fire conditions
- Compressed Gases: None
- Pressure at Room Temperature: Does not apply

**6. Accidental Release Measures**

- Steps to be taken in cases of spill or leak:  
Wear proper personal protective equipment. Remove any sources of ignition from the area and allow hot surfaces to cool. Return uncontaminated material to metal container and seal container tightly. Dispose of contaminated material or waste. Clean up with mineral spirits.

**7. Handling and Storage**

- Storage: Cool, dry, storage below 90 degrees F. Store in closed containers. Refrigerate for best shelf life.
- Handling: Avoid contact with skin and eyes. Do not breathe vapors. This product in its purchased form does not create an inhalation hazard from fibers or dust. If grinding or sanding or any other process is performed to this compound will cause airborne particles wear appropriate respirator to avoid breathing any dust or vapors. Wear appropriate safety gear as required in work area.

**8. Exposure Controls / Personal Protection**

Exposure Limits Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
Solvent Mixture	100ppm TWA	500ppm TWA	
Modified Natural Resins	10mg/m3	15mg/m3	

**Personal Protective Equipment (PPE)**

Eyes: Safety Glasses  
Full face shield recommended. (if injecting under pressure)

Skin: Chemical resistant gloves such as impervious butyl or nitrile rubber gloves.

**Respiratory Protection:**

NIOSH approved for organic vapors and dust.

**Other Protective Clothing or Equipment:**

Coveralls or other protective clothing. Safety equipment as required in area.

Work / Hygienic Practices: Avoid contact with skin. Wash hands before eating.

Engineering Controls : Ventilation: Local exhaust if poorly ventilated area or in confined spaces.  
Ventilation should be provided during heat up to exhaust organic vapors resulting from vaporization of certain organic agents

**9. Chemical and Physical Properties**

Appearance:	Thin Brown Liquid
Odor:	Solvent like
pH:	5.2
Solubility in Water:	NIL
Specific Gravity:	1.0 (uncured) (H <sub>2</sub> O =1)
Evaporation Rate:	Not Applicable
Boiling Point:	Not Applicable
Melting Point:	Not Applicable
Vapor Pressure:	Solvent only, mixture not tested : 0.6 kPa (2.2 mm Hg) at 20 C
Vapor Density:	Solvent only, mixture not tested 5.5 (air =1)
VOC Content:	Max 29% by weight
Flash Point:	160 <sup>0</sup> F. Method: ASTM D93 Pensky-Martens Closed Cup

**Flammable Limits:**

LEL: Not Established  
UEL: Not Established

**10. Stability and Reactivity**

Stability:	Stable
Hazardous Polymerization:	Will not occur
Hazardous Decomposition	
Or By-Products:	CO, CO <sub>2</sub> , H <sub>2</sub> S, SO <sub>2</sub> , Smoke, Incomplete Combustion Products
Incompatibility:	Strong Oxidizers and Strong Acids, Mineral Acids, Alkalies,

**11. Toxicology Information**

Primary Routes of Entry: Inhalation and contact.  
Signs and Symptoms of Overexposure: **Inhalation:** Possible dizziness or headaches, respiratory irritation. **Eyes:** Redness and irritation.  
**Skin:** Chemical dermatitis, redness and itching.

Existing Conditions Aggravated by Exposure: Pre-existing skin condition if prolonged exposure to skin. (Wear chemical resistant gloves) Respiratory disorders, asthma, chronic emphysema, heart condition (if prolonged and continuous exposure to dust or vapors).  
Dust exposure is not a hazard with this product under normal use.  
Product is in a liquid form. (Organic vapors , Wear recommended respirator if exceeding permissible exposure limit, see section 8

Carcinogenicity  
NTP: None  
IARC: None  
OSHA Regulated: NO

Toxicity : (Solvent only, mixture not tested)  
Inhalation (Solvent): Low Toxicity: LC50 greater than near-saturated vapor concentration / 1 hour rat  
Skin (Solvent): Expected to be of Low Toxicity : LD50.2000 mg/kg, Rat mg/kg, rat  
Ingestion: (Solvent): Expected to be of Low Toxicity : LD50>2000 mg/kg, rat

Acute Health Hazards: **Skin:** Contact on bare skin can cause chemical dermatitis, redness, itching  
**Inhalation:** Breathing excessive vapors may cause dizziness or headaches irritation of eyes, nose, throat, lungs and can cause central nervous system depression.

Chronic Health Hazards: **Inhalation:** Crystalline Silica, respirable size NTP Known Carcinogen.  
Repeated exposure to solvent vapors above recommended exposure limits, can cause central nervous system effects, drowsiness, dizziness and headaches.  
(Wear recommended respirator if exceeding permissible exposure limit, see section 8)

**12. Ecological Information**

Solvent Only : Expected to have low toxicity. LC/EC/IC50 > 1000 mg/l, Fish, Aquatic Invertebrates, Algae, Microorganisms.  
Mobility - Absorbs to soil and has low mobility. Floats on water.

**13. Disposal Considerations**

Recommended Methods of Disposal:  
RCRA 40 CFR 261 Classification : This product as purchased does not fall under current US EPA RCRA definitions of Hazardous Waste. Contains solvent, do not let waste contaminate soil or water.  
Certain state regulations could affect whether a material is considered a hazardous waste upon disposal. It must also be noted that a material can become a hazardous waste if it is mixed with or comes in contact with a hazardous substance during use. Under RCRA it is the responsibility of user of a product to determine at the time of disposal, whether a material should be classified as a hazardous waste.

**14. Transport Information**

DOT (49 CFR 172): Not Regulated\*  
\*Not Regulated under 49 CFR if in a container of 119 gallon capacity or less.

IATA : Not Regulated

Liquid / Solid (per ASTM D 4359-90) : Material is a liquid

**15. REGULATORY INFORMATION**

CERCLA HAZARDOUS SUBSTANCES (40 CFR Part 302.4): This product is not reportable under 40 CFR Part 302.4.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR Part 355): This product does not contain any SARA 302 Extremely Hazardous Substances.

SARA TITLE III SECTION 311/312 HAZARDOUS CATEGORIZATION (40 CFR Part 370): Certain ingredients of this product are regulated under Sara Title III Section 311/312, see section 3 of this MSDS.

SARA TITLE III SECTION 313 (40 CFR Part 372): None

U.S. INVENTORY (TSCA): Any chemical substances (as defined in 40 CFR Part 710.2), that are contained in, or used in the manufacture of this product, are reported in the EPA TSCA Inventory. (As required per 40 CFR 710.3)

CALIFORNIA PROPOSITION 65: None

CANADA WHMIS: Ingredient Disclosure List: Solvent Mixture 64742-47-8, WHMIS Classification: Solvent B3

EUROPEAN UNION : Solvent 64742-47-8:CLP Asp Tox 1

OZONE DEPLETERS: \* This product is not manufactured with or contains any Class I or Class II Ozone Depleting Chemicals. (ODC's)

**16. OTHER INFORMATION**

The information contained in this MSDS sheet is based upon data supplied by our suppliers and data determined by us in our facilities at the time these products were formulated. We have reviewed any information that we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety data in this sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. If after reviewing this MSDS you have determined that this product poses unusual risks to you, your plant, or your plant personnel, or if you cannot comply fully with all safety recommendations, do not use this product. This product is intended for a temporary repair. The responsibility for whether or not the product is suitable for use rest solely with the purchaser. We recommend that the product be tested prior to use. Your use of this information is beyond our control, therefore, the information is provided without warranty expressed or implied. We accept no liability beyond the purchase price of the material.

**Estimated HMIS® Code:**

Health Hazard: \* 1  
Flammability Hazard: 2  
Physical Hazard: 0

\* See section 11 for chronic effects.

Personal Protection: NPCA recommends that PPE codes be determined by the employer, who is familiar with the actual conditions under which chemicals in the facility are used.

**Procedural Warning:**

Attn: Technician

(For Industrial use Only)

Avoid contact with skin and eyes. See section 8 of SDS for personal protective equipment.

Ventilation may be needed during heating/curing stage to exhaust organic vapors resulting from vaporization of certain organic agents. Always avoid direct contact with smoke and vapors being emitted from the compound during the heating/curing process. These vapors may be irritating to the skin, eyes and respiratory system. It is quite common that the application temperature will exceed the uncured compound flash point. Be aware of the possibility of a flash and take necessary precautions.

Read product technical data and safety information before using product.

**PREPARATION INFORMATION**

Prepared By: Safety Department  
Company: Jet-Lube LLC / Deacon  
Revision Date: 03-31-15 Revision: F