

3. Composition / Information on Ingredients

Ingredients	CAS No.	% by weight
Dimethyl siloxane, hydroxy-terminated	70131-67-8	25-50
Iron Oxide	1337-37-2	25-50
Diatomaceous Earth, Flux Calcined	68855-54-9	25-50
Cristobalite	14464-46-1	1-20
Tetrapropyl orthosilicate	682-01-9	< 10
Quartz	14808-60-7	< 2

4. First Aid Measures

- Ingestion: DO NOT INGEST. If irritation or discomfort occur, obtain medical advice.
- Inhalation: if symptoms are experienced, remove victim to fresh air. If symptoms persist, seek medical attention.
- Skin Contact: no health affects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
- Eye Contact: If irritation does occur, flush eyes with lukewarm, gently flowing water for 5 minutes. If symptoms persist, seek medical attention.

5. Fire Fighting Measures

Recommended Extinguishing Agent:

Foam, Dry Chemical, Carbon Dioxide, Water Fog

Special Fire Fighting Procedures:

Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. (Professionally Trained Personnel).

Hazardous Products Formed by Fire or Thermal Decomposition:

Thermal breakdown during a fire can evolve the following decomposition products: Silicon Dioxide, Formaldehyde, Metal Oxides, Quartz

Unusual Fire or Explosion Hazards: None

Compressed Gases: None

Pressure at Room Temperature: Does not apply

6. Accidental Release Measures

Steps to be taken in cases of spill or leak:

Wear proper personal protective equipment. Remove any sources of ignition from the area and allow hot surfaces to cool. Return uncontaminated material to container and seal container tightly. May present a slip hazard, clean up with a suitable absorbant. Dispose of contaminated material or waste.

7. Handling and Storage

Storage: Cool, dry, storage away from water and moisture. Keep out of reach of children. Store in closed containers.

Handling: Avoid contact with skin and eyes. Do not breathe heated vapors, do not take internally. This product in its purchased form does not create an inhalation hazard from dust. If grinding or sanding or any other process is performed to this compound when cured, will cause airborne particles wear appropriate respirator to avoid breathing any dust or vapors. Wear appropriate safety gear as required in work area.

8. Exposure Controls / Personal Protection

Exposure Limits Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
Dimethyl siloxane, hydroxy-terminated	Not established	Not Established	
Iron Oxide	5 mg/m3 as FE TWA Inhalable particulate	10 mg/m3 (Iron Oxide fume)	
Diatomaceous Earth, Flux Calcined	May contain silica quartz (see quartz below)		
Cristobalite	0.05 mg/m3 (respirable)	0.025 mg/m3 (respirable)	
Tetrapropyl orthosilicate	10 ppm TWA	100 ppm TWA	
Quartz	0.1 mg/m3 (respirable)	0.025 mg/m3 (respirable)	

Items below are not ingredients but possible by-products:

Formaldehyde (When heated to temperatures above 180 C in the presence of open air, product can form formaldehyde vapors.)
 Formaldehyde is a potential cancer causer and a known skin and respiratory sensitizer.
 Formaldehyde 1 ppm TWA .75 ppm TWA
 2 ppm STEL

n-Propyl alcohol is formed upon contact with water or humid air. Provide adequate ventilation to control exposure within guidelines of OSHA PEL (final rule) : TWA 200 ppm, STEL 250 ppm ACGIH TLV: TWA 100 ppm

Personal Protective Equipment (PPE)

Eyes: Safety Glasses
 Full face shield recommended. (during injection process)
 Skin: Chemical resistant gloves

Respiratory Protection: NIOSH approved air purifying respirator with an organic vapor cartridge or canister may be permissible under circumstances where airborne concentrations are expected to exceed exposure limits.

Other Protective Clothing or Equipment:

Coveralls or other protective clothing. Safety equipment as required in area.

Work / Hygienic Practices:

Avoid contact with skin and eyes. Avoid breathing vapors. Wash hands before eating.

Engineering Controls : Ventilation: Local exhaust if poorly ventilated area or in confined spaces.
 General ventilation recommended.

NOTE: THIS PRODUCT IN ITS PURCHASED FORM DOES NOT PRESENT AN INHALATION HAZARD FROM DUST, AS IT IS A LIQUID, DUST IS NOT AIRBORN UNDER NORMAL HANDLING.

9. Chemical and Physical Properties

Appearance: red liquid
 Odor: slight odor
 pH: 7.0 (cured rubber)
 Solubility in Water: Insoluble
 Specific Gravity: 1.48 (H2O =1)
 Evaporation Rate: Not Applicable
 Boiling Point: >65 C
 Melting Point: Not Applicable
 Vapor Pressure: Not Applicable
 Vapor Density: Not Established
 VOC Content: None
 Viscosity : 27,500 mPa's
 Flash Point: >212⁰ F. (closed cup)

Flammable Limits:

LEL: Not Established
 UEL: Not Established

10. Stability and Reactivity

Stability: Stable
 Hazardous Polymerization: Will not occur
 Hazardous Decomposition Or By-Products: Thermal breakdown during a fire can evolve the following decomposition products: Silicon Dioxide, Formaldehyde, Metal Oxides, Quartz
 Incompatibility: Strong Oxidizers and Some Acids

11. Toxicology Information

Primary Routes of Entry: Inhalation and skin contact.
 Signs and Symptoms of Overexposure: **Inhalation:** Irritates respiratory passages very slightly
Eyes: Direct contact may cause temporary redness and discomfort
Skin : None Known
Ingestion: None Known
 Existing Conditions Aggravated by Exposure: None Known

Carcinogenicity

NTP: Crystalline Silica, respirable size (Cristobalite and Quartz) Known to be a Carcinogen
 IARC: Silica Dust in form of Cristobalite and Quartz, Group 1 IARC
 OSHA Regulated: NO
 Toxicity : Not Determined

Acute Health Hazards: **Skin:** Possible irritation.
Inhalation: Irritates respiratory passages very slightly
Eyes: Direct contact may cause temporary redness and discomfort

Chronic Health Hazards: None Known during normal use. see **NOTE** below.

NOTE: THIS PRODUCT IN ITS PURCHASED FORM DOES NOT PRESENT AN INHALATION HAZARD FROM DUST, AS IT IS A LIQUID, DUST IS NOT AIRBORN UNDER NORMAL HANDLING.

12. Ecological Information

Complete information is not available

13. Disposal Considerations

Recommended Methods of Disposal:
 RCRA 40 CFR 261 Classification : This product as purchased does not fall under current US EPA RCRA definitions of Hazardous Waste.
 Certain state regulations could affect whether a material is considered a hazardous waste upon disposal. It must also be noted that a material can become a hazardous waste if it is mixed with or comes in contact with a hazardous substance during use. Under RCRA it is the responsibility of user of a product to determine at the time of disposal, whether a material should be classified as a hazardous waste.

14. Transport Information

DOT (49 CFR 172): Not Regulated
 IATA : Not Regulated
 Liquid / Solid (per ASTM D 4359-90) : Material is a Liquid

15. REGULATORY INFORMATION

CERCLA HAZARDOUS SUBSTANCES (40 CFR Part 302.4): None

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR Part 355): This product does not contain any SARA 302 Extremely Hazardous Substances.

SARA TITLE III SECTION 311/312 HAZARDOUS CATEGORIZATION (40 CFR Part 370): Certain ingredients of this product are regulated under Sara Title III Section 311/312, see section 3 of this MSDS.

SARA TITLE III SECTION 313 (40 CFR Part 372): None

U.S. INVENTORY (TSCA): Any chemical substances (as defined in 40 CFR Part 710.2), that are contained in, or used in the manufacture of this product, are reported in the EPA TSCA Inventory. (As required per 40 CFR 710.3)

CALIFORNIA PROPOSITION 65: Crystalline Silica (Cristobalite and Quartz)
Formaldehyde (When heated to temperatures above 180 C in the presence of open air, product can form formaldehyde vapors.) **Not an ingredient, but a possible by-product**

EUROPEAN UNION : Dimethyl siloxane, hydroxy-terminated: CLP Skin Irritant 2, Eye irritant 2
Iron Oxide : CLP Acute Toxicity 4, STOT RE1.
Diatomaceous Earth, Flux Calcined: CLP STOT RE1
Cristobalite : CLP STOT RE2
Tetrapropyl orthosilicate: CLP Skin Irritant 2, Eye Irritant 2
Quartz : CLP STOT RE2

Items below are not ingredients but possible by-products:

Formaldehyde (When heated to temperatures above 180 C in the presence of open air, product can form formaldehyde vapors.) : CLP Acute Tox 3, Carc.2
n-Propyl alcohol is formed upon contact with water or humid air. : CLP Flam Liquid 2, Eye Damage 1, STOT SE3

CANADA WHMIS: Ingredient Disclosure List : : Crystalline Silica, quartz -- Crystalline Silica, Cristobalite, Diatomaceous Earth, Formaldehyde (When heated to temperatures above 180 C in the presence of open air, product can form formaldehyde vapors.) **Not an ingredient, but a possible by-product** n-Propyl alcohol is formed upon contact with water or humid air
Not an ingredient, but a possible by-product

WHMIS Classification: Crystalline Silica, quartz:, D2A, Crystalline Silica, Cristobalite D2A, Diatomaceous Earth D2A

OZONE DEPLETERS: * This product is not manufactured with or contains any Class I or Class II Ozone Depleting Chemicals. (ODC's)

16. OTHER INFORMATION

The information contained in this MSDS sheet is based upon data supplied by our suppliers and data determined by us in our facilities at the time these products were formulated. We have reviewed any information that we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety data in this sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. If after reviewing this MSDS you have determined that this product poses unusual risks to you, your plant, or your plant personnel, or if you cannot comply fully with all safety recommendations, do not use this product. This product is intended for a temporary repair. The responsibility for whether or not the product is suitable for use rest solely with the purchaser. We recommend that the product be tested prior to use. Your use of this information is beyond our control, therefore, the information is provided without warranty expressed or implied. We accept no liability beyond the purchase price of the material.

Estimated HMIS® Code:

Health Hazard:	1
Flammability Hazard:	1
Physical Hazard:	0
Personal Protection:	NPCA recommends that PPE codes be determined by the employer, who is familiar with the actual conditions under which chemicals in the facility are used.

PREPARATION INFORMATION

Prepared By:	Safety Department
Company:	Jet-Lube LLC / Deacon
Revision Date:	10-06-14 Revision: C