

## 7228

<b>Description:</b>	Thread Sealant / Gasket Sealant Paste
<b>Temperature Range:</b>	-25° F. to +450° F.
<b>Applications:</b>	For use on Threaded Connections, Flanges, Cover Plates, Valve Cover Gaskets, and any Metal to Metal Joints.
<b>Chemical Compatibility:</b>	Excellent Resistance to Oils, Water, Steam, Di-Ester Type Fluids, Diesel Fuels, Gasoline, Greases, Ethylene Glycol, Transmission Fluid, and Aliphatic Hydrocarbons.
<b>Features:</b>	Viscous Paste, Slow Drying, Remains Pliable, Improves Reliability, Extends Gasket Life, Stops Leakage, Will Not Interfere with Future Repairs or Maintenance.
<b>Shelf Life:</b>	Two Years in Closed Containers.
<b>Packaged:</b>	10.3 fl. oz. Caulking Tube, Pint Brush Top, Quart

**FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.**

CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE.

**NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

Disclaimer: The information & recommendations of Jet-Lube LLC / Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Jet-Lube LLC / Deacon, the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Jet-Lube LLC / Deacon recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.

[info@deaconindustries.com](mailto:info@deaconindustries.com) (800) 552-2896 or (724) 225-8008