

Date Prepared: February 1, 2017

**1. Product and Company Identification**

Jet-Lube LLC / Deacon  
Bldg. #1, West Point Drive  
Washington, PA 15301 USA  
Phone (724) 225-8008

**24 Hour Emergency Response Contact:**  
**CHEMTREC** (USA and CANADA)  
**Phone: 800-424-9300** or 703-527-3887

Product Name: Deacon Dry-Pak 16  
Product Type: Aramid Pulp Dry Mixture  
Product Description: Yellow Mixture  
General Use : Sealant Additive

**2. Hazards Identification****GHS Classification :**

Skin Irritation, 2  
Eye Irritation, 2B

**GHS Label Elements :**

Signal Word : Warning

**Hazard Statements:**

H315 / 320 Can cause Skin and Eye Irritation

**Precautionary Statements :**

P261 Avoid breathing dust  
P262 Do not get in eyes, on skin, or on clothing  
P285 In case of inadequate ventilation wear respiratory protection  
P281 Use personal protective equipment as required  
P301/P312 If Swallowed: Call a poison center or doctor if you feel unwell  
P302/P352 If on skin: Wash with plenty of soap and water  
P333/P313 If skin irritation or rash develops: Get medical attention.  
P305/P351/P338 If in eyes : Rinse cautiously with water for several minutes.  
Remove contact lenses if easy to do. Continue Rinsing.  
P337/P313 If eye irritation persists: Get medical attention  
P233 Keep container tightly closed  
P501 Dispose of observing all Federal, State and Local regulations.

---

**3. Composition / Information on Ingredients**

Ingredients	CAS No.	% by weight
Para-aramid pulp	26125-61-1	100

**4. First Aid Measures**

Ingestion: DO NOT INGEST. Oral toxicity of mixture not determined.  
Call a physician or get medical help.

Inhalation: Remove to fresh air. consult physician if symptoms develop.

Skin Contact: Wash with soap and water, consult physician if irritation develops.

Eye Contact: Flush with water 15 minutes. If symptoms persist, seek medical attention.

**5. Fire Fighting Measures**

Recommended Extinguishing Agent:  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special Fire Fighting Procedures:  
Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. (Professionally Trained Personnel).

Hazardous Products Formed by Fire or Thermal Decomposition:  
>300 C (>572 F) CO<sub>2</sub>, Nitrogen oxides, Hydrogen Cyanide (gaseous), Ammonia, Aldehydes, Hydrocarbons

Unusual Fire or Explosion Hazards: None

Compressed Gases: None  
Pressure at Room Temperature: Does not apply

**6. Accidental Release Measures**

Steps to be taken in cases of spill or leak:  
Wear proper personal protective equipment. Remove any sources of ignition from the area and allow hot surfaces to cool. Return uncontaminated material to container and seal container tightly. Dispose of contaminated material or waste.

**7. Handling and Storage**

Storage: Cool, dry, storage. Store in closed containers

Handling: Avoid contact with skin and eyes.  
Wear appropriate respirator if necessary, to avoid overexposure.  
Wear appropriate safety gear as required in work area.

**8. Exposure Controls / Personal Protection**

Exposure Limits

Ingredients:

Para-aramid pulp	Acceptable Exposure Limits* 2 fibers/cm <sup>3</sup> 8 & 12 hr TWA (Respirable Fibers) 5 mg/m <sup>3</sup> 8 & 12 hr. TWA (Non-Fibrous particulate and/or non respirable fibers)
------------------	--

\*AEL is the manufacturers Acceptable Exposure Limit, where governmentally imposed occupational exposure limits are lower than the AEL are in effect, such limits shall take precedence.

Personal Protective Equipment (PPE)

Eyes: Safety Glasses  
Full face shield recommended. (during injection process)

Skin: Chemical resistant gloves.

Respiratory Protection: If necessary, NIOSH approved for dust.

Other Protective Clothing or Equipment: Coveralls or other protective clothing. Safety equipment as required in area..

Work / Hygienic Practices: Avoid contact with skin. Wash hands before eating or smoking.

Engineering Controls : Ventilation: Local exhaust if poorly ventilated area or in confined spaces.

**9. Chemical and Physical Properties**

Appearance:	Yellow Fiber
Odor:	No Odor
pH:	Not Established
Solubility in Water:	NIL
Specific Gravity:	1.44-1.45 (H <sub>2</sub> O =1)
Evaporation Rate:	Not Applicable
Boiling Point:	Not Applicable
Melting Point:	Not Applicable
Vapor Pressure:	Not Established
Vapor Density:	Not Established
VOC Content:	None (under 300 C)
Flash Point:	Not Applicable Method: None

Flammable Limits:

LEL: Not Established

UEL: Not Established

**10. Stability and Reactivity**

Stability:	Stable
Hazardous Polymerization:	Will not occur
Hazardous Decomposition Or By-Products:	>300 C (>572 F) CO <sub>2</sub> , Nitrogen oxides, Hydrogen Cyanide (gaseous), Ammonia, Aldehydes, Hydrocarbons
Incompatibility:	Strong Oxidizers and Strong bases

**11. Toxicology Information**

Primary Routes of Entry: Inhalation and contact.  
Signs and Symptoms of Overexposure: **Inhalation:** Dust can cause respiratory irritation.  
**Eyes:** Redness and discomfort  
**Skin:** Discomfort, redness and itching.

Existing Conditions Aggravated  
by Exposure: None Known

Carcinogenicity  
NTP: None present at 0.1% or greater  
IARC: None present at 0.1% or greater  
OSHA Regulated: NO

Toxicity : (Not a toxicity hazard in purchased state and under recommended usage limits)

Skin : No skin irritation : Rabbit  
Ingestion : ALD >7500 mg/kg, Rat  
Eye : Non-irritant

Acute Health Hazards: Skin: Continual rubbing of fibers and dust on skin can cause mild irritation  
with redness or itching  
Inhalation: May cause respiratory tract irritation. (dust)  
Prolonged exposure to high concentrations of dust may cause  
respiratory tract irritation. consult physician if symptoms develop.

Chronic Health Hazards: None Known

**12. Ecological Information**

No known eco-toxicology effects.

**13. Disposal Considerations**

RCRA 40 CFR 261 Classification : This product as purchased does not fall under current US EPA RCRA definitions of Hazardous Waste.

It is recommended that if this product in its purchased form is going to become a waste, that it be disposed of by a licensed waste disposal company, observing all Federal, State and Local regulations. Can be landfilled or incinerated. Additionally, certain state regulations could affect whether a material is considered a hazardous waste upon disposal. It must also be noted that a material can become a hazardous waste if it is mixed with or comes in contact with a hazardous substance during use. Under RCRA it is the responsibility of user of a product to determine at the time of disposal, whether a material should be classified as a hazardous waste.

**14. Transport Information**

DOT (49 CFR 172): Not Regulated

IATA : Not Regulated

Liquid / Solid (per ASTM D 4359-90) : Material is a solid

**15. REGULATORY INFORMATION**

CERCLA HAZARDOUS SUBSTANCES (40 CFR Part 302.4): This product is not reportable under 40 CFR Part 302.4.

SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR Part 355): This product does not contain any SARA 302 Extremely Hazardous Substances.

SARA TITLE III SECTION 311/312 HAZARDOUS CATEGORIZATION (40 CFR Part 370): Certain ingredients of this product are regulated under Sara Title III Section 311/312, see section 3 of this MSDS.

SARA TITLE III SECTION 313 (40 CFR Part 372): None

U.S. INVENTORY (TSCA): Any chemical substances (as defined in 40 CFR Part 710.2), that are contained in, or used in the manufacture of this product, are reported in the EPA TSCA Inventory. (As required per 40 CFR 710.3)

CALIFORNIA PROPOSITION 65: None

CANADA WHMIS: This product does not contain any substances listed on the WHMIS ingredient disclosure list.

EUROPEAN UNION : None

OZONE DEPLETERS: \* This product is not manufactured with or contains any Class I or Class II Ozone Depleting Chemicals. (ODC's)

**16. OTHER INFORMATION**

The information contained in this MSDS sheet is based upon data supplied by our suppliers and data determined by us in our facilities at the time these products were formulated. We have reviewed any information that we received from sources outside our company. We believe that information to be correct but cannot guarantee its accuracy or completeness. Health and safety data in this sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. If after reviewing this MSDS you have determined that this product poses unusual risks to you, your plant, or your plant personnel, or if you cannot comply fully with all safety recommendations, do not use this product. This product is intended for a temporary repair. The responsibility for whether or not the product is suitable for use rest solely with the purchaser. We recommend that the product be tested prior to use. Your use of this information is beyond our control, therefore, the information is provided without warranty expressed or implied. We accept no liability beyond the purchase price of the material.

**Estimated HMIS® Code:**

Health Hazard:	0
Flammability Hazard:	0
Physical Hazard:	0
Personal Protection:	NPCA recommends that PPE codes be determined by the employer, who is familiar with the actual conditions under which chemicals in the facility are used.

**Procedural Warning:**

Attn: Technician

(For industrial use by professionally trained personnel only) When the compound is curing, vapors and gasses are given off and should be vented. Steps should be taken to insure that the injection pressure in conjunction with pressure that may occur from gassing off does not exceed the pressure limitations of the piping system. Also, be aware it is quite common that the application temperature will exceed the compound flash point. Be aware of the possibility of a flash and take necessary precautions. Avoid contact with skin and eyes. See section 8 of SDS for personal protective equipment. Ventilation may be needed during heating/curing stage to exhaust organic vapors resulting from vaporization of certain organic agents. Always avoid direct contact with smoke and vapors being emitted from the compound during the heating/curing process. These vapors may be irritating to the skin, eyes and respiratory system. Read product technical data and safety information before use.

**PREPARATION INFORMATION**

Prepared By:	Safety Department
Company:	Jet-Lube LLC / Deacon
Revision Date:	05-01-15 Revision: C