

## Mold-Pac™

<b>Description:</b>	DEACON Mold-Pac™ is a Damming, Molding, and Positioning Putty.
<b>Features:</b>	Resistant to extreme temperatures, Can be easily and quickly removed, Remains flexible and retains molten Babbitt and low melting point materials, Easily packed in place, Holds tight, Asbestos-free.
<b>Applications:</b>	Damming compound (for pouring Babbitt bearings, epoxies, various molten alloys, etc.), Vibration suppression, Positioning delicate parts, Holding solder while soldering wires on generators, Aids in positioning during welding/brazing.
<b>Packaging:</b>	10 lb. container, 50 lb. pail
<b>Shelf Life:</b>	Two years
<b>Notes:</b>	Thicker version available (Mold-Pac™HD) in bulk and extruded diameters.  Mold-Pac™EDM recommended for use on Mineral Oil and various Dielectric Fluids.



**FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.**

CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE.

**NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

Disclaimer: The information & recommendations of Jet-Lube LLC / Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Jet-Lube LLC / Deacon, the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Jet-Lube LLC / Deacon recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.

[info@deaconindustries.com](mailto:info@deaconindustries.com) (800) 552-2896 or (724) 225-8008