

4437

Description:	PTFE / Kevlar® / Graphite based Sealant / Packing. Dense, fibrous non-curing compound with good lubricity.
Temperature Range:	-40 degrees F. to 450 degrees F.
Applications:	Packing for valves. Steam service, water service, chemical processes. (Not for use on Oxidizing Chemicals)
Characteristics:	Good chemical resistance, good bridging capabilities, good lubricity, non-curing, remains flexible. Can be hand packed or injected.
Shelf Life:	2 years in closed containers.
Packaged:	Quarts, and 5/8" x 3" plugs. Other sizes available upon request.
Directions:	Please be advised that we recommend a top and bottom ring of braided packing still be installed for containment, especially when tolerances are in question.

Kevlar® is a registered trademark of DuPont Corp.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT MSDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE.

NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS

Disclaimer: The information & recommendations of Jet-Lube LLC / Deacon concerning these products is based upon laboratory tests, customer feedback, and experience and to the best of our knowledge and belief are true and accurate. As the conditions of use are beyond the control of Jet-Lube LLC / Deacon, the company assumes no liability for damage caused by this product other than the replacement of the product or refund of the purchase price. The responsibility for determining whether or not the product is suitable for use rest solely with the purchaser. Jet-Lube LLC / Deacon recommends that the product be tested prior to use. This product is intended for a temporary repair and no agent, representative or employee of the company is authorized to alter this provision which relates to goods delivered, whether sold, delivered as samples or otherwise.

info@deaconindustries.com (800) 552-2896 or (724) 225-8008